



## TECHNICAL SPECIFICATIONS

**Dimensions:** 54-56 cm seat centres  
52 cm depth  
97 cm height

**Backrest:** Cold moulded polyurethane foam, which wraps an injected polypropylene frame completely. It is later upholstered by means of a fabric cover, everything is protected by a compressed wood cover. Polyurethane density 55 Kg/m<sup>3</sup>.

**Seat:** Cold moulded polyurethane foam, which wraps an injected polypropylene frame completely. It is later upholstered by means of a fabric cover. The seat pan folds by means of an automatic noiseless maintenance-free double spring. Polyurethane density 65 Kg/m<sup>3</sup>.

**Side panel:** Wood fibres board, finish in beech. Concealed floor fixation system.


**Armrest:** Included in the very side panel.

**Volume:** 0.160 m<sup>3</sup>/unit


**Weight:** 26.00 Kg not assembled



**DRAWING**



**OPTIONS**



**CERTIFICATES**

	Fabrics	Fire Barrier	Foam	Seat
BS 5852:2006	•			
BS-EN 1021-1:2006	•			
CAL TB 117-2013, SECTION 1	•			
UNE 23.727-90 1R (M1)	•	•		
UNE-EN 1021-1:2006 / UNE-EN 1021-2:2006	•	•	•	•
BS 5852:1979 Parte 1		•		
Acoustic absorption coefficient		•		•



Euro Seating reserves the right to modify the dimensions and characteristics without prior notice. All dimensions and specifications are given for information purposes only.